

**Section 1. Chemical Product and Company Identification**

Product Number: S2 Series  
Product Name: HAZMAT Sorbent Products

**Manufacturer:**  
NPS Corporation  
3303 Spirit Way  
Green Bay, WI 54304

**Emergency Telephone Numbers:**  
CHEMTREC--Domestic (800)424-9300 24 hours  
--International (202)483-7616 24 hours  
Information (800) 558-5066 7:30am-4:30pm CDT M-

F

**Section 2. Composition/Information on Ingredients**

<u>CAS Registry #</u>	<u>Component</u>	
9003-07-0	Polypropylene Particulate or Fabric	98.7%
---NA---	Yellow Pigment	0.3%
---NA---	Surfactant	1.0%

(NOTE: See Section 8 of this MSDS for Exposure Guidelines)

**Section 3. Hazards Identification**

**Emergency Overview**  
Odorless, white or colored fabric or particulate. This material presents little or no hazard if spilled and exhibits no unusual fire hazard.

**Potential Health Effects**

- Eye: Direct contact may cause irritation.
- Inhalation: Exposure to dust levels exceeding the PEL (see Section 8) may cause irritation of the upper respiratory system. Breathing dust may aggravate acute or chronic asthma or other chronic pulmonary diseases.
- Signs and Symptoms:
  - Eyes: Redness, Tearing
  - Inhalation: Dry cough, labored breathing during exertion

**Section 4. First Aid Measures**

- Eye: Immediately flush with plenty of water for at least 15 minutes. If irritation persists, seek medical attention.
- Skin: Brush off excess fibers with dry towel. Wash affected area with plenty of soap and water for several minutes. If skin irritation develops or persists, seek medical attention.
- Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention.

**NOTE:** If burned through contact with molten material, cool as quickly as possible with water and seek medical attention. Do not attempt to remove the cooled molten material.

---

## Section 5. Fire Fighting Measures

Flash Point: >625 °F

Flammable Limits: NA

Auto-ignition Temperature: >675 °F

**NOTE:** This material will burn, but it is difficult to ignite.

Extinguishing Media: Water spray, ABC dry chemical, foam, or carbon dioxide. Use water fog or spray to cool exposed equipment and containers.

Special Fire Fighting Procedures: For large fires or fires in confined areas, full emergency equipment with self-contained breathing apparatus and full protective clothing should be used. Thermal decomposition of this product may produce hazardous and irritating gases. See Section 10.

---

## Section 6. Accidental Release Measures

Unused material can be shoveled, swept, or vacuumed and recycled for use. Avoid generating airborne dust.

If used material is released or spilled, see Section 13.

---

## Section 7. Handling and Storage

Store at room temperature in a dry area. When handling, avoid the generation of airborne dust. Storage for extended periods (>30 days) at temperatures >150 °F may cause decomposition. This material produces an electrostatic accumulation hazard. Use proper grounding/bonding procedures.

---

## Section 8. Exposure Controls/Personal Protection

Exposure Limits: None specifically developed for this product; treated as a nuisance dust as defined in 29 CFR 1910.1000.

OSHA PEL: Total Dust is 15 mg/M<sup>3</sup>.

Respirable Fraction is 5mg/M<sup>3</sup>.

ACGIH TLV is 10 mg/M<sup>3</sup>.

The end-user must determine the specific types of personal protective equipment needed according to 29 CFR 1910.132—Personal Protective Equipment (PPE) for General Industry. The following are only suggestions:

- Eyes: Safety glasses or goggles
- Skin: Work gloves

Adequate ventilation should be provided to limit the amount of airborne dust.

---

## Section 9. Physical and Chemical Properties

Appearance: White or colored fabric or particulate

Odor: Odorless

Boiling Point: NA

Vapor Pressure (mmHg): NA

Vapor Density: NA

Solubility in Water: Insoluble

Specific Gravity (H<sub>2</sub>O=1): 0.90

Melting Point: >320 °F

pH: NA

Evaporation Rate (Butyl Acetate=1): NA

% Vaporizable by volume (H<sub>2</sub>O=100): <0.4

---

# MATERIAL SAFETY DATA SHEET

---

**Section 10. Stability and Reactivity**

Stable: Yes

Conditions to Avoid: See Section 7

Incompatibility (Materials to Avoid): Avoid contact with hot or concentrated nitric and perchloric acids, and fuming sulfuric acid at temperatures >140 °F

Hazardous Decomposition or Byproducts: Thermal decomposition produces carbon monoxide, carbon dioxide, methane, acetone, and other ketones.

Hazardous Polymerization: Will not occur

---

**Section 11. Toxicological Information**

This product is not listed by NTP or IARC. See Section 15.

---

**Section 12. Ecological Information**

No data available. See Section 15.

---

**Section 13. Disposal Considerations**

This product in itself is considered to be non-hazardous as defined by RCRA (40 CFR 261). Once used, this product will take on the characteristics of the chemical sorbed and should be disposed of accordingly.

Disposal of this product (used or unused) must be in compliance with all local, state, and federal regulations.

---

**Section 14. Transport Information**

This product is not a DOT Hazardous Material and is not regulated for all shipping purposes.

---

**Section 15. Regulatory Information**

This product does not meet the definition of a hazardous chemical given in 29 CFR 1910.1200 (OSHA).

TSCA Inventory Status: All components are listed on the TSCA list.

SARA Title III

Section 302 Extreme Hazardous Substance List: Not listed

Section 311/312 Hazard Classification:

Immediate (acute): No

Delayed (chronic): No

Fire: No

Sudden Release of Pressure: No

Reactive: No

Section 313 Toxic Chemicals: Not listed

USEPA CERCLA—Reportable Quantity (RQ): Not listed

RCRA Hazardous Waste: Not listed

State/Int'l Right-to-Know Regulations: Not listed

---

**Section 16. Other Information**

Abbreviations:

CFR: Code of Federal Regulations

OSHA: Occupational Safety and Health Administration

MSDS: Material Safety Data Sheet

PEL: Permissible Exposure Limit

NA: Not Applicable

ACGIH: American Conference of Governmental Industrial Hygienists

TLV: Threshold Limit Value

NTP: National Toxicology Program

---

**MATERIAL SAFETY DATA SHEET**

**Abbreviations (cont.):**

IARC: International Agency for Research on Cancer  
RCRA: Resource Conservation and Recovery Act  
TSCA: Toxic Substances Control Act  
SARA: Superfund Amendments and Reauthorization Act  
USEPA: United States Environmental Protection Agency  
CERCLA: Comprehensive Response, Compensation, and Liability Act  
DOT: Department of Transportation  
NFPA: National Fire Protection Association  
HMIS: Hazardous Material Information System

**NFPA Ratings:**

Health: 0  
Fire: 1  
Reactivity: 0  
Special Hazard: None

**HMIS Ratings:**

Health: 0  
Flammability: 1  
Reactivity: 0  
Personal Protection: NA

**NOTE:** This MSDS has been prepared only for the Hazmat Sorbent Products (S2 Series) of SPILFYTER® Products. The MSDS's of the chemicals used with this product must be reviewed completely, and precautions taken as described.

The information accumulated herein has been compiled from sources believed to be reliable and is accurate to the best of our knowledge. However, NPS Corporation cannot give guarantees regarding the information from sources, and expressly does not make any warranties, nor assumes any liability for its uses of this product.

**Disclaimer**

You have purchased SPILFYTER® products from NPS Corporation  
You have been provided data, product labels, MSDS's, and other information about SPILFYTER® Products.

Some SPILFYTER® Products are hazardous. Information about SPILFYTER® Products that are hazardous is furnished without guarantee. NPS Corporation does not guarantee the accuracy of the information about hazardous SPILFYTER® Products.

Those products are only to be used by people having expertise in using the hazardous products.

The information provided about the hazardous products is believed to be correct. You must perform your investigation as to the safety, toxicity, suitability, and proper shipping method for any hazardous SPILFYTER® Product.

No guarantee, expressed or implied, is made by NPS Corporation about the results of use of its products. No guarantee is made as to the safety and toxicity of any SPILFYTER® Product.

NPS Corporation does not assume any liability arising out of use of SPILFYTER® Products. Additional information and research may be necessary before you use the SPILFYTER® Products. NPS Corporation is not responsible for damages, direct or indirect, resulting from the use of SPILFYTER® Products or from reliance on data in the MSDS or product label.

**MATERIAL SAFETY DATA SHEET**

If you resell SPILFYTER® Products, you must, by law, furnish your customers a copy of MSDS's and handling instructions.

You are also required by law to insure that all SPILFYTER® Products are properly shipped.

SPILFYTER®, KOLLECT-A-KEM®, HANDS-IN-BAG®, KOLORSAFE®, and GRAB&GO® are all registered trademarks of NPS Corporation  
 AQUALOCKIT™, TRUK-KIT™, DRAIN GUARD™, GAPSEAL™, MEDICLEAN™, and TIDYMAT™, are all trademarks of NPS Corporation

© Copyright 2002, NPS Corporation

## MATERIAL SAFETY DATA SHEET

SPILFYTER® Products  
 KOLORSAFE® Liquid Acid Neutralizer

Page 1 of 5  
 Revision Date: 07/19/05  
 MSDS No. 1006

### Section 1. Chemical Product and Company Identification

Product Number: 4100 Series  
 Product Name: KOLORSAFE® Liquid Acid Neutralizer

**Manufacturer:**  
 NPS Corporation  
 3303 Spirit Way  
 Green Bay, WI 54304

**Emergency Telephone Numbers:**  
 CHEMTREC--Domestic (800)424-9300 24 hours  
 --International (202)483-7616 24 hours  
 Information (800) 558-5066 7:30am-4:30pm CDT M-F

### Section 2. Composition/Information on Ingredients

<u>CAS Registry #</u>	<u>Component</u>
102-71-6	Triethanolamine
72-48-0	Alizarin
7732-18-5	Water

(NOTE: See Section 8 of this MSDS for Exposure Guidelines)

### Section 3. Hazards Identification

#### Emergency Overview

Purple liquid with an ammonia-like odor. This product presents no unusual fire hazard.

#### **Potential Health Effects**

- Eye: May cause slight to severe irritation.
- Skin: May cause slight to severe irritation. Repeated skin contact may aggravate an existing dermatitis (skin condition) and/or sensitivity of the skin.
- Inhalation: Exposure to vapors or mists in excess of the TLV (see Section 8) or in unusually high concentrations generated from spraying, heating the material, or from exposure in poorly ventilated areas or confined spaces may cause irritation of the nose, throat, and upper respiratory system.
- Signs and Symptoms:
- Eyes: Redness, Tearing

- Skin: Redness, Swelling
- Inhalation: Discomfort of the nose and throat, headache, nausea, and drowsiness

---

#### Section 4. First Aid Measures

Eyes: Immediately flush with plenty of water for at least 15 minutes. If irritation persists, seek medical attention.

Skin: Remove contaminated clothing. Wash affected area with plenty of soap and water for several minutes. If skin irritation develops or persists, seek medical attention.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention.

Ingestion: If swallowed, call a physician or poison control center immediately.

---

## MATERIAL SAFETY DATA SHEET

SPILFYTER® Products  
KOLORSAFE® Liquid Acid Neutralizer

Page 2 of 5  
Revision Date: 07/19/05  
MSDS No. 1006

---

#### Section 5. Fire Fighting Measures

Flash Point: Not Tested

Flammable Limits: Not Tested

Auto-ignition Temperature: Not Tested

**NOTE:** This material is non-flammable as supplied.

Extinguishing Media: Water spray, ABC dry chemical, foam, or carbon dioxide. Use water fog or spray to cool exposed equipment and containers. Water or foam may cause frothing.

Special Fire Fighting Procedures: For large fires or fires in confined areas, full emergency equipment with self-contained breathing apparatus and full protective clothing should be used. Thermal decomposition of this product may produce hazardous or irritating byproducts. See Section 10.

---

#### Section 6. Accidental Release Measures

Avoid breathing vapors. Avoid contact with skin, eyes, or clothing. Contain the spill and collect the material using chemically resistant sorbent products. If this product is mixed with other materials, see Section 13.

---

#### Section 7. Handling and Storage

Avoid high heat and/or freezing conditions. Keep container tightly closed. Suitable for general chemical storage under normal warehouse conditions.

**NOTE:** If this product is stored at temperatures >150 °F or at elevations above 5000 feet, gas may form, increasing the pressure within the container, causing the container to bulge. If bulging occurs, remove the container from the work area and slowly open the container to release the gas. Be sure to wear proper personal protective equipment.

---

#### Section 8. Exposure Controls/Personal Protection

Exposure Limits: Triethanolamine  
ACGIH TLV is 5 mg/M<sup>3</sup>.  
OSHA PEL: Not Established

The end-user must determine the specific types of personal protective equipment needed according to 29 CFR 1910.132—Personal Protective Equipment (PPE) for General Industry. The following are only suggestions:

- Eyes: Safety glasses, goggles, or face shield
- Skin: Suitable chemically resistant gloves and protective clothing
- Inhalation: Air purifying respirator with appropriate chemical cartridge or canister

Adequate ventilation should be provided to meet the ACGIH exposure limits.

---

#### Section 9. Physical and Chemical Properties

Appearance: Purple liquid  
Odor: Ammonia-like odor  
Boiling Point: 218 °F

Evaporation Rate (Butyl Acetate=1): Not Tested  
% Vaporizable by volume (H<sub>2</sub>O=100): 100

Vapor Pressure (mmHg): Not Tested  
Vapor Density: Not Tested  
Solubility in Water: Soluble  
Specific Gravity (H<sub>2</sub>O=1): 1.09  
Freezing Point: -4 °F  
pH: 10.2

---

## MATERIAL SAFETY DATA SHEET

SPILFYTER® Products  
KOLORSAFE® Liquid Acid Neutralizer

Page 3 of 5  
Revision Date: 07/19/05  
MSDS No. 1006

---

### Section 10. Stability and Reactivity

Stable: Yes

Conditions to Avoid: See Section 7

Incompatibility (Materials to Avoid): None known

Hazardous Decomposition or Byproducts: In a limited air supply, thermal decomposition produces carbon monoxide, carbon dioxide, ammonia, irritating aldehydes and ketones.

Hazardous Polymerization: Will not occur

---

### Section 11. Toxicological Information

This product is not listed by NTP or IARC. See Section 15.

---

### Section 12. Ecological Information

No data available. See Section 15.

---

### Section 13. Disposal Considerations

This product in itself is considered to be non-hazardous as defined by RCRA (40 CFR 261). Once used, this product may take on the characteristics of the chemical(s) it was used with and should be disposed of accordingly. Disposal of this product (used or unused) must be in compliance with all local, state, and federal regulations.

---

### Section 14. Transport Information

Not regulated by DOT

---

### Section 15. Regulatory Information

TSCA Inventory Status: All components are listed on the TSCA list.

SARA Title III

Section 302 Extreme Hazardous Substance List: Not listed

Section 311/312 Hazard Classification:

Immediate (acute): Yes

Delayed (chronic): No

Fire: No

Sudden Release of Pressure: No

Reactive: No

Section 313 Toxic Chemicals: Not listed

USEPA CERCLA—Reportable Quantity (RQ): Not listed

RCRA Hazardous Waste: Not listed

State/Int'l Right-to-Know Regulations: Canada's WHMIS—Triethanolamine 1%

California Proposition 65: Not listed

International Regulations: All components are listed on the following lists:

- Canada Inventory Status: Canadian Domestic Substance (DSL)
- European Inventory of Existing Chemical Substances (EINECS)

---

---

# MATERIAL SAFETY DATA SHEET

SPILFYTER® Products  
KOLORSAFE® Liquid Acid Neutralizer

Page 4 of 5  
Revision Date: 07/19/05  
MSDS No. 1006

---

## Section 16. Other Information

### Abbreviations:

CFR: Code of Federal Regulations  
OSHA: Occupational Safety and Health Administration  
MSDS: Material Safety Data Sheet  
PEL: Permissible Exposure Limit  
NA: Not Applicable  
ACGIH: American Conference of Governmental Industrial Hygienists  
TLV: Threshold Limit Value  
NTP: National Toxicology Program  
IARC: International Agency for Research on Cancer  
RCRA: Resource Conservation and Recovery Act  
TSCA: Toxic Substances Control Act  
SARA: Superfund Amendments and Reauthorization Act  
USEPA: United States Environmental Protection Agency  
CERCLA: Comprehensive Response, Compensation, and Liability Act  
DOT: Department of Transportation  
WHMIS: Workplace Hazardous Materials Information System  
n.o.s.: Not Otherwise Specified  
NFPA: National Fire Protection Association  
HMIS: Hazardous Material Information System

### NFPA Ratings:

Health: 1  
Fire: 1  
Reactivity: 0  
Special Hazard: None

### HMIS Ratings:

Health: 1  
Flammability: 1  
Reactivity: 0  
Personal Protection: X

**NOTE:** This MSDS has been prepared only for the KOLORSAFE® Liquid Acid Neutralizer (4100 Series) of SPILFYTER® Products. The MSDS's of the chemicals used with this product must be reviewed completely, and precautions taken as described.

The information accumulated herein has been compiled from sources believed to be reliable and is accurate to the best of our knowledge. However, NPS Corporation cannot give guarantees regarding the information from sources, and expressly does not make any warranties, nor assumes any liability for its uses of this product.

### Disclaimer

You have purchased SPILFYTER® products from NPS Corporation  
You have been provided data, product labels, MSDS's, and other information about SPILFYTER® Products.

Some SPILFYTER® Products are hazardous. Information about SPILFYTER® Products that are hazardous is furnished without guarantee. NPS Corporation does not guarantee the accuracy of the information about hazardous SPILFYTER® Products.

Those products are only to be used by people having expertise in using the hazardous products.

# MATERIAL SAFETY DATA SHEET

SPILFYTER® Products  
KOLORSAFE® Liquid Acid Neutralizer

Page 5 of 5  
Revision Date: 07/19/05  
MSDS No. 1006

The information provided about the hazardous products is believed to be correct. You must perform your investigation as to the safety, toxicity, suitability, and proper shipping method for any hazardous SPILFYTER® Product.

No guarantee, expressed or implied, is made by NPS Corporation about the results of use of its products. No guarantee is made as to the safety and toxicity of any SPILFYTER® Product.

NPS Corporation does not assume any liability arising out of use of SPILFYTER® Products. Additional information and research may be necessary before you use the SPILFYTER® Products. NPS Corporation is not responsible for damages, direct or indirect, resulting from the use of SPILFYTER® Products or from reliance on data in the MSDS or product label.

If you resell SPILFYTER® Products, you must, by law, furnish your customers a copy of MSDS's and handling instructions.

You are also required by law to insure that all SPILFYTER® Products are properly shipped.

SPILFYTER®, KOLLECT-A-KEM®, HANDS-IN-BAG®, KOLORSAFE®, and GRAB&GO® are all registered trademarks of NPS Corporation  
AQUALOCKIT™, TRUK-KIT™, DRAIN GUARD™, GAPSEAL™, MEDICLEAN™, and TIDYMAT™ are all trademarks of NPS Corporation

Copyright 2001, NPS Corporation

# MATERIAL SAFETY DATA SHEET

SPILFYTER® Products  
AQUALOCKIT®

Page 1 of 5  
Revision Date: 03/31/05  
MSDS No. 1016

## Section 1. Chemical Product and Company Identification

Product Number: 6700 Series  
Product Name: AQUALOCKIT™--Super Polymer

**Manufacturer:**  
NPS Corporation  
3303 Spirit Way  
Green Bay, WI 54304

**Emergency Telephone Numbers:**  
CHEMTREC--Domestic (800)424-9300 24 hours  
--International (202)483-7616 24 hours  
Information (800) 558-5066 7:30am-4:30pm CDT M-F

## Section 2. Composition/Information on Ingredients

<u>CAS Registry #</u>	<u>Component</u>
25608-12-2	Potassium Polyacrylate

(NOTE: See Section 8 of this MSDS for Exposure Guidelines)

## Section 3. Hazards Identification

### Emergency Overview

Odorless, white crystalline solid. This material presents little or no hazard if spilled and exhibits no unusual fire hazard.

#### Potential Health Effects

**NOTE:** This product polymerizes water. Avoid contact with eyes and mucous membranes.

Eye: May cause irritation.

Skin: May cause irritation.

Inhalation: Exposure to dust levels exceeding the PEL (see Section 8) may cause irritation to the upper respiratory system.

Signs and Symptoms:

- Eyes: Redness, Tearing
- Skin: Redness
- Inhalation: Shortness of breath, Labored breathing

---

## Section 4. First Aid Measures

Eyes: Immediately flush with plenty of water for at least 15 minutes. If irritation persists, seek medical attention.

Skin: Brush off excess powder with a dry towel. Wash affected area with plenty of soap and water for several minutes. If skin irritation develops or persists, seek medical attention.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention.

Ingestion: If swallowed, call a physician or poison control center immediately.

---

## MATERIAL SAFETY DATA SHEET

SPILFYTER® Products  
AQUALOCKIT®

Page 2 of 5  
Revision Date: 03/31/05  
MSDS No. 1016

---

## Section 5. Fire Fighting Measures

Flash Point: NA

Flammable Limits: NA

Auto-ignition Temperature: NA

**NOTE:** This material is non-combustible as supplied and will not support combustion. This material is slippery when wet.

Extinguishing Media: Any extinguishing media can be used for the packaging.

Special Fire Fighting Procedures: For large fires or fires in confined areas, full emergency equipment with self-contained breathing apparatus and full protective clothing should be used. Thermal decomposition will produce carbon monoxide, carbon dioxide, and hydrocarbons.

---

## Section 6. Accidental Release Measures

Avoid breathing or generating airborne dust. Avoid using water. Avoid contact with eyes and mucous membranes. If unused material is spilled, collect by sweeping, shoveling or vacuuming and recycle the material for use. If this product is mixed with other materials, see Section 13.

---

## Section 7. Handling and Storage

Store in a cool, dry, and well ventilated area.

---

---

## Section 8. Exposure Controls/Personal Protection

Exposure Limits: None specifically developed for this product; treated as a nuisance dust as defined in 29 CFR 1910.1000.

OSHA PEL: Total Dust is 15 mg/M<sup>3</sup>.  
Respirable Fraction is 5mg/M<sup>3</sup>.  
ACGIH TLV is 10 mg/M<sup>3</sup>.

The end-user must determine the specific types of personal protective equipment needed according to 29 CFR 1910.132—Personal Protective Equipment (PPE) for General Industry. The following are only suggestions:

- Eyes: Safety glasses or goggles
- Skin: Suitable chemically resistant gloves and protective clothing
- Inhalation: Air purifying respirator with appropriate filter for nuisance dust.

Adequate ventilation should be provided to limit the threat of inhalation.

---

---

## Section 9. Physical and Chemical Properties

Appearance: White crystalline solid

Odor: Odorless

Boiling Point: NA

Vapor Pressure (mmHg): NA

Vapor Density: NA

Solubility in Water: Insoluble—polymerizes water

Specific Gravity (H<sub>2</sub>O=1): 0.90

Melting Point: NA

pH: NA

Evaporation Rate (Butyl Acetate=1): NA

% Vaporizable by volume (H<sub>2</sub>O=100): NA

---

---

# MATERIAL SAFETY DATA SHEET

SPILFYTER® Products  
AQUALOCKIT®

Page 3 of 5  
Revision Date: 03/31/05  
MSDS No. 1016

---

## Section 10. Stability and Reactivity

Stable: Yes

Conditions to Avoid: None known

Incompatibility (Materials to Avoid): Strong oxidizers

Hazardous Decomposition or Byproducts: Thermal decomposition produces carbon monoxide, carbon dioxide, and hydrocarbons.

Hazardous Polymerization: Will not occur

---

---

## Section 11. Toxicological Information

This product is not listed by NTP or IARC. See Section 15.

---

---

## Section 12. Ecological Information

No data available. See Section 15.

---

---

## Section 13. Disposal Considerations

This product in itself is considered to be non-hazardous as defined by RCRA (40 CFR 261). Once used, this product may take on the characteristics of the chemical(s) sorbed and should be disposed of accordingly.

Disposal of this product (used or unused) must be in compliance with all local, state, and federal regulations.

---

---

## Section 14. Transport Information

This product is not a DOT Hazardous Material and is not regulated for all shipping purposes.

---

---

## Section 15. Regulatory Information

TSCA Inventory Status: All components are listed on the TSCA list.

SARA Title III

Section 302 Extreme Hazardous Substance List: Not listed

Section 311/312 Hazard Classification:

Immediate (acute): No

Delayed (chronic): No

Fire: No

Sudden Release of Pressure: No

Reactive: No

Section 313 Toxic Chemicals: Not listed

USEPA CERCLA—Reportable Quantity (RQ): Not listed

RCRA Hazardous Waste: Not listed

State/Int'l Right-to-Know Regulations: Not listed

---

## Section 16. Other Information

Abbreviations:

CFR: Code of Federal Regulations

OSHA: Occupational Safety and Health Administration

MSDS: Material Safety Data Sheet

PEL: Permissible Exposure Limit

NA: Not Applicable

ACGIH: American Conference of Governmental Industrial Hygienists

TLV: Threshold Limit Value

NTP: National Toxicology Program

IARC: International Agency for Research on Cancer

## MATERIAL SAFETY DATA SHEET

SPILFYTER® Products

AQUALOCKIT®

Page 4 of 5

Revision Date: 03/31/05

MSDS No. 1016

---

Abbreviations (cont.):

RCRA: Resource Conservation and Recovery Act

TSCA: Toxic Substances Control Act

SARA: Superfund Amendments and Reauthorization Act

USEPA: United States Environmental Protection Agency

CERCLA: Comprehensive Response, Compensation, and Liability Act

DOT: Department of Transportation

NFPA: National Fire Protection Association

HMIS: Hazardous Material Information System

NFPA Ratings:

Health: 1

Fire: 0

Reactivity: 0

Special Hazard: None

HMIS Ratings:

Health: 1

Flammability: 0

Reactivity: 0

Personal Protection: X

**NOTE:** This MSDS has been prepared only for the AQUALOCKIT™ (6700 Series) of SPILFYTER® Products. The MSDS's of the chemicals used with this product must be reviewed completely, and precautions taken as described.

The information accumulated herein has been compiled from sources believed to be reliable and is accurate to the best of our knowledge. However, NPS Corporation cannot give guarantees regarding the information from sources, and expressly does not make any warranties, nor assumes any liability for its uses of this product.

**Disclaimer**

You have purchased SPILFYTER® products from NPS Corporation

You have been provided data, product labels, MSDS's, and other information about SPILFYTER® Products.

Some SPILFYTER® Products are hazardous. Information about SPILFYTER® Products that are hazardous is furnished without guarantee. NPS Corporation does not guarantee the accuracy of the information about hazardous SPILFYTER® Products.

Those products are only to be used by people having expertise in using the hazardous products.

The information provided about the hazardous products is believed to be correct. You must perform your investigation as to the safety, toxicity, suitability, and proper shipping method for any hazardous SPILFYTER® Product.

No guarantee, expressed or implied, is made by NPS Corporation about the results of use of its products. No guarantee is made as to the safety and toxicity of any SPILFYTER® Product.

NPS Corporation does not assume any liability arising out of use of SPILFYTER® Products. Additional information and research may be necessary before you use the SPILFYTER® Products. NPS Corporation is not responsible for damages, direct or indirect, resulting from the use of SPILFYTER® Products or from reliance on data in the MSDS or product label.

**MATERIAL SAFETY DATA SHEET**

SPILFYTER® Products  
AQUALOCKIT®

Page 5 of 5  
Revision Date: 03/31/05  
MSDS No. 1016

---

If you resell SPILFYTER® Products, you must, by law, furnish your customers a copy of MSDS's and handling instructions.

You are also required by law to insure that all SPILFYTER® Products are properly shipped.

SPILFYTER®, KOLLECT-A-KEM®, HANDS-IN-BAG®, KOLORSAFE®, and GRAB&GO® are all registered trademarks of NPS Corporation  
AQUALOCKIT™, TRUK-KIT™, DRAIN GUARD™, GAPSEAL™, MEDICLEAN™, and TIDYMAT™ are all trademarks of NPS Corporation

Copyright 2001, NPS Corporation

---